

Direct-Vent Cast Iron Stoves









Millivolt or Intermittent Pilot

Empire Stoves are available in two types of ignition – Millivolt (MV) and Intermittent Pilot (IP). The Millivolt system lights a standing pilot with a pushbutton piezo ignitor. Once the standing pilot is lit, the MV system operates with an on/off switch concealed on the back of the burner or with one of the optional remote control systems listed on the back of this brochure. The standing pilot allows your Empire stove to provide heat during power outages.

IP systems eliminate the standing pilot for even greater energy savings. Pressing the on/off switch ignites the pilot, which then ignites the main burner. IP systems can also operate with an optional remote control system.

Includes AC adaptor with battery backup. The continuous pilot switch allows your Empire stove to provide heat during extended power outages.

Medium Size Stoves

Our medium stoves are rated at 27,000 Btu and stand just over three feet tall. The richly detailed casting features fully operable decorative cast iron doors on durable lift-pin hinges that swing open 180 degrees.

Choose from five finishes – porcelain black, porcelain mahogany, porcelain sand, matte black, and matte pewter.

Each of our porcelain stoves starts with a hand-applied pigment and glass mixture that's oven fired to 1,500 degrees Fahrenheit to produce a rich durable finish that both softens and highlights edges. Our porcelain finishes capture and reflect room light for exceptional visual interest. The porcelain mahogany finish features light and dark accents, for added visual interest.

Our matte finishes, in pewter or black, give your stove a more contemporary look that shows off every exquisitely intricate line and edge of the casting, from the geometric crosshatch detail to the raised ribs along the classically curved legs.

Compact Size Stoves

Our compact stoves stand two feet tall and are rated at 20,000 Btu – ideal for heating smaller spaces.

The casting features all the rich detail of the medium stove but has non-operable doors.

Compact Empire Stoves and available matching shelves come in three finishes – porcelain black, porcelain mahogany, and matte black.

Accessories

The optional side shelf sets, available in every stove color, install in seconds to create an old-world look for your Empire stove.

Add a black porcelain liner to any medium or compact stove to create even more "depth" and visual interest.

Floor pads are available but not required. You can place your Empire Stove directly on carpet or tile.





TOP LEFT: Empire Medium Direct-Vent Stove in Porcelain Black with optional Side Shelves.

TOP RIGHT: Empire Compact
Direct-Vent Stove in Porcelain Mahogany.

IMMEDIATE RIGHT: The hand-painted ceramic fiber log set of the Empire Medium Direct-Vent Stove.

FAR RIGHT: Optional Matching Side Shelf Kits add scale and detail to any Empire stove.





Empire Cast Iron Stove Finish Options		3,4				
Stove Size	Control	Porcelain Black	Porcelain Mahogany	Matte Black	Porcelain Sand	Matte Pewter
Compact	Millivolt	DVP-20-CC30B	DVP-20-CC30M	DVP-20-CC30F	N/A	N/A
Compact	Intermittent Pilot	DVP-20-CC70B	DVP-20-CA70M	DVP-20-CC70F	N/A	N/A
Medium	Millivolt	DVP-30-CC30B	DVP-30-CC30M	DVP-30-CC30F	DVP-30-CC30S	DVP-CC30W
Medium	Intermittent Pilot	DVP-30-CC70B	DVP-30-CC70M	DVP-30-CC70F	DVP-30-CC70S	DVP-CC70W

Stone Colors for Inlays & Floor Pads	Adobe Frost Granite	Patina Mocha Tile	American Beauty Marble	Temple Gray Marble	Venetian Gold Granite
Stone Inlay for Medium Stove (replaces metal grill inlay on Medium Stoves only)	CSI-9A	CSI-10M	CSI0-12A	CSI-11G	CSI-8V
Traditional Floor Pad Stone Inlay Kit (CIFPB-1)	CIFS-10M	CIFS-10A	CIFS-12A	CIFS-11G	CIFS-8V
Corner Floor Pad Stone Inlay Kit (CIFPB-1C)	CIFS-9AC	CIFS-10MC	CIFS-12AC	CIFS-11GC	CIFS-8VC


Direct-Vent Technology

Empire direct-vent models use standard 4 x 6 5/8 vent pipe and generate sufficient heat to warm any room in your home or provide total heat for a small cabin. Your dealer can help you determine your heating requirements. A direct-vent system draws in outdoor air to support combustion and sends its exhaust directly outdoors. The versatile direct-vent technology allows your dealer to install your stove with vertical or horizontal venting. All DV Empire installations require a 45° elbow.

All Empire Cast Iron Stove ships assembled in one carton, for easier set-up.

Empire Cast Iron Stoves are now available in two sizes – compact (DVP20) and medium (DVP30).

Cast Iron Stove Shelf Kits (fit compact and medium stoves, includes left and right shelf)						
CSK-B	Porcelain Black					
CSK-F	Matte Black					
CSK-M	Porcelain Mahogany					
CSK-S	Porcelain Sand					
CSK-W	Matte Pewter					
Accessories						
CIB-3	Automatic Variable Speed Blower. Fits Medium Cast Iron Stove.					
CIB-4	Automatic Variable Speed Blower. Fits Compact Cast Iron Stove.					
DVP-20-CCK	Liner, Porcelain Black, fits DVP-20-CC Stoves					
DVP-30-CCK	Liner, Porcelain Black, fits DVP-30-CC Stoves					
DVKHP-1	Direct-Vent Kit for Horizontal Run (See Price List for Vent Kit Details)					
DVKVP-1	Direct-Vent Kit for Vertical Run (See Price List for Vent Kit Details)					
Control	Options					
FRBC	Battery Operated Remote Control					
FRBTC	Battery Operated Remote Control with Thermostat					
FREC	Electric Remote					
FWS-1	On/Off Wall Switch					
TMV	Wall Thermostat - Reed Switch					
TRW	Wall Thermostat - Wireless Remote					



Model	A	В	\mathbf{C}	D
DVP-20-CC	21 1/2	32 3/4	24 1/8	15 3/8
DVP-30-CC	28 1/16	37	27 3/4	17 1/8

Clearance to Combustible Materials					
Side Wall 6 in.		Adjacent Corner Wall	4 in.		
Back Wall	2 in.	Ceiling	36 in.		

Gas Inlet

Type of Gas (State on Order)

Iron Pipe Size (N.P.T.)

Ignition System

Natural or LP

1/2-inch DVP

Standing Pilot/Piezo or Intermittent Pilot

Warranty

All vented parts carry a 3-year limited warranty.

Note: Empire Comfort Systems is committed to continuous product improvement; specifications are subject to change without notice. Flame size, shape and color will vary from photos.

Member of the following industry associations:



RKVN

RKVP







Converts Manual Variable to Remote Variable (Natural)

Converts Manual Variable to Remote Variable (LP)

This appliance is design-certified to the ANSI standard by:





918 Freeburg Ave. Belleville, IL 62220-2623 E-mail: info@empirecomfort.com ECS-00915 04/01/14