



LPG

HEATING



SPECIFICATIONS

MODEL/SIZE (LBS.)	100	200	420
HEIGHT (IN.)	48	40	52
HEIGHT (MM)	1,219	1,016	1,321
LPG CAPACITY (GAL.)	23.6	47.2	99.1
LPG CAPACITY (LITER)	89.3	178.7	375.1
WATER CAPACITY (LBS.)	239	474	1,000
WATER CAPACITY (KG)	108.4	215	454
NOMINAL TARE WEIGHT (LBS.)	68	142	271
NOMINAL TARE WEIGHT (KG)	30.8	64.4	122.9
CYLINDER DIAMETER (IN.)	14.7	24	30
CYLINDER DIAMETER (MM)	373	610	762
CYLINDER VOLUME (CU. IN.)	6,616	13,120	27,680
CYLINDER VOLUME (LITER)	108.4	215	454
COLLAR DIAMETER (IN.)	6.5	16	16
COLLAR DIAMETER (MM)	165	406	406
COLLAR HEIGHT (IN.)	5.1	6.9	6.9
COLLAR HEIGHT (MM)	130	175	175
FOOTRING DIAMETER (IN.)	14.5	19	22
FOOTRING DIAMETER (MM)	368	483	559
STANDARD SPECIFICATION	DOT-4BW-240	DOT-4BW-240	DOT-4BW-240

All dimensions are approximate.



LPG

SYSTEM



SPECIFICATIONS

MODEL/SIZE (LBS.)	100	100 SQUAT	200	420
HEIGHT (IN.)	50	35	40	52
HEIGHT (MM)	1,270	889	1,016	1,321
LPG CAPACITY (GAL)	23.6	23.6	47.2	99.1
LPG CAPACITY (LITER)	89.3	89.3	178.7	375.1
WATER CAPACITY (LBS.)	239	239	474	1,000
WATER CAPACITY (KG)	108.4	108.4	215	454
MAWP* (PSIG)	250	250	250	250
MAWP* (BAR)	17	17	17	17
CYLINDER DIAMETER (IN.)	14.5	18	24	30
CYLINDER DIAMETER (MM)	369	457	610	762
CYLINDER VOLUME (CU. IN.)	6,629	6,629	13,120	27,680
CYLINDER VOLUME (LITER)	108.7	108.7	215	454
COLLAR DIAMETER (IN.)	11.4	16	16	16
COLLAR DIAMETER (MM)	290	406	406	406
COLLAR HEIGHT (IN.)	6.4	6.9	6.9	6.9
COLLAR HEIGHT (MM)	163	175	175	175
FOOTRING DIAMETER (IN.)	14.5	16.6	19	22
FOOTRING DIAMETER (MM)	368	422	483	559
STANDARD SPECIFICATION	ASME	ASME	ASME	ASME

*MAWP = Maximum Allowable Working Pressure